

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.20.2020

Page 1 of 13

Sunset Glow

SECTION 1: Identification

Product identifier

Product name: Sunset Glow

Recommended use of the product and restriction on use

Relevant identified uses: Marine - Automotive Detail Spray n Wax

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

Auto Glanz US
6692 Kies St. NE
Rockford, Michigan 49341
616-502-1900
www.autoglanzus.com

Emergency telephone number:

United States

CHEMTREC
1-800-424-9300 (24 hrs)
1-800-262-8200 (24 hrs)
1-703-527-3887 (24 hrs (international))

SECTION 2: Hazard(s) identification

GHS classification:

Skin irritation, category 2
Flammable liquids, category 4
Eye irritation, category 2A
Acute toxicity (oral), category 4

Label elements

Hazard pictograms:



Signal word: Warning

Hazard statements:

H227 Combustible liquid
H315 Causes skin irritation
H319 Causes serious eye irritation
H302 Harmful if swallowed

Precautionary statements:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.20.2020

Page 2 of 13

Sunset Glow

P264 Wash hands/skin thoroughly after contact with or handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking
P270 Do not eat, drink or smoke when using this product
P302+P352 IF ON SKIN: WASH WITH PLENTY OF SOAP AND WATER.
P321 Specific treatment (see first aid procedures on the product label in section 4 of this SDS)
P332+P313 If skin irritation occurs: Get medical advice/attention
P362 Take off contaminated clothing and wash it before reuse
P370+P378 In case of fire: Use water spray or foam to extinguish [water jet not recommended].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337+P313 If eye irritation persists: Get medical advice/attention
P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
P330 Rinse mouth
P403+P235 Store in a well-ventilated place. Keep cool
P501 Dispose of contents/container in accordance with local, state and federal regulations.

Hazards not otherwise classified: None

SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 7732-18-5	Water	90
CAS number: 111-76-2	2-Butoxyethanol	1-5
CAS number: Proprietary	Surfactant blend	1-5
CAS number: 67-63-0	Propan-2-ol	1
CAS number: N/A	Functional-siloxanes, terminated	1-5
CAS number: 63148-62-9	Dimethyl siloxane	1-5

Additional Information: None

SECTION 4: First aid measures

Description of first aid measures

General notes:

Show this Safety Data Sheet to the doctor in attendance.

Show this Safety Data Sheet to the doctor in attendance. Take precautions to ensure your own safety before attempting rescue. Wear appropriate safety eyewear, gloves, protective clothing and respiratory protection to prevent exposure. See Section 8 of this SDS for personal protective equipment recommendations. Do not use the mouth to mouth method if victim has ingested or inhaled the product. Give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper device.

After inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.20.2020

Page 3 of 13

Sunset Glow

rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

After skin contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

After eye contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

Rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

Rinse eyes with plenty of water for several minutes. Remove contact lenses, if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

After swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Skin contact may result in redness, pain, burning and inflammation.

Product is highly flammable. Exposure to sources of ignition may cause physical injury.

Eye contact may result in irritation, redness, pain, inflammation, itching, burning and tearing.

Acute oral exposure may lead to dizziness, drowsiness, headache, breathing difficulties, nausea, vomiting, abdominal pain, and lowering of consciousness. Adverse effects are dependent on exposure (dose, concentration, contact time).

Delayed symptoms and effects:

Effects are dependent on exposure (dose, concentration, contact time).

Symptoms of exposure may be delayed.

Immediate medical attention and special treatment

Specific treatment:

Skin/eye burns require immediate treatment.

Notes for the doctor:

Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Dry chemical, CO₂, water spray or alcohol-resistant foam.

Unsuitable extinguishing media:

Do not use water jet.

Specific hazards during fire-fighting:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.20.2020

Page 4 of 13

Sunset Glow

Thermal decomposition may produce irritating/toxic fumes/gases.

Combustible liquid. Will be easily ignitable by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation.

Special protective equipment for firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

Evacuate non-essential personnel. Ventilate closed spaces before entering. Consider initial evacuation for 300 meters in all directions. If tank/rail car is involved in the fire, ISOLATE for 800 meters in all directions. Fight fire from a maximum distance. Move containers from fire area if you can do it without risk. Use water spray/fog for cooling fire exposed containers. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Always stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles. If this is impossible, withdraw from area and let fire burn. Stand by, at a safe distance, with extinguisher ready for possible re-ignition. A vapor-suppressing foam may be used to reduce vapors. Avoid unnecessary run-off of extinguishing media which may cause pollution. Do not handle damaged containers unless specialized to do so.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. All equipment used when handling the product must be grounded. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Do not get on skin, eyes or on clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Remove contaminated clothing and launder before reuse.

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and material for containment and cleaning up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. A vapor-suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Harmful if swallowed. Do not touch damaged containers or spilled material unless wearing appropriate

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.20.2020

Page 5 of 13

Sunset Glow

personal protective clothing. Avoid breathing dust, mist, fumes, vapors or spray. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and storage

Precautions for safe handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating and lighting equipment. Take action to prevent static discharges. Handle containers with caution. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for safe storage, including any incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
OSHA	2-Butoxyethanol	111-76-2	8-Hour TWA-PEL: 25 ppm
	2-Butoxyethanol	111-76-2	8-Hour TWA-PEL: 240 mg/m ³
	Propan-2-ol	67-63-0	8-Hour TWA-PEL: 400 ppm (OSHA PEL TWA 980 mg/m ³)
NIOSH	2-Butoxyethanol	111-76-2	IDLH: 700 ppm
	2-Butoxyethanol	111-76-2	TWA: 5 ppm (REL (for up to a 10 hour work day))
	2-Butoxyethanol	111-76-2	TWA: 24 mg/m ³ (REL (for up to a 10 hour work day))
	Propan-2-ol	67-63-0	IDLH: 2000 ppm
	Propan-2-ol	67-63-0	15-Minute STEL: 500 ppm (1,225 mg/m ³)
	Propan-2-ol	67-63-0	REL-TWA: 400 ppm (980 mg/m ³ - up to 10 hrs.)
ACGIH	2-Butoxyethanol	111-76-2	8-Hour TWA: 20 ppm
	Propan-2-ol	67-63-0	15-Minute STEL: 400 ppm
	Propan-2-ol	67-63-0	8-Hour TWA: 200 ppm
United States(California)	2-Butoxyethanol	111-76-2	8-Hour TWA-PEL: 20 ppm (OSHA (California))

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.20.2020

Page 6 of 13

Sunset Glow

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	2-Butoxyethanol	111-76-2	8-Hour TWA-PEL: 97 mg/m ³ (OSHA (California))
	Propan-2-ol	67-63-0	8-Hour TWA-PEL: 980 mg/m ³ (400 ppm - Cal/OSHA)
	Propan-2-ol	67-63-0	15-Minute STEL: 1225 mg/m ³ (500 ppm - Cal/OSHA)

Biological limit values:

Country (Legal Basis)	Substance	Identifier	Determinant	Specimen	Sampling time	Permissible limits
ACGIH	2-Butoxyethanol	111-76-2	Butoxyacetic acid (BAA) in urine (with hydrolysis) - (creatinine)	Creatinine in Urine	End of shift	200 mg/g

Information on monitoring procedures:

Not determined or not applicable.

Appropriate engineering controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal protection equipment

Eye and face protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and body protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

General hygienic measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Translucent, White Liquid
------------	---------------------------

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.20.2020

Page 7 of 13

Sunset Glow

Odor	Tropical Coconut
Odor threshold	Not determined or not available.
pH	4.0-6.0
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	>60c-<93c
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	0.98-1.0
Relative density	Not determined or not available.
Solubilities	Water
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

Other information

SECTION 10: Stability and reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical stability:

Stable under recommended handling and storage conditions.

Possibility of hazardous reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Extreme heat, open flames, hot surfaces, sparks, ignition sources, static electricity and incompatible materials. Vapor accumulation in low or confined areas.

Incompatible materials:

None known.

Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity

Assessment:

Harmful if swallowed.

Product data: No data available.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.20.2020

Page 8 of 13

Sunset Glow

Substance data:

Name	Route	Result
2-Butoxyethanol	oral	LD50 Rat: 470 mg/kg
	dermal	LD50 Rabbit: 220 mg/kg
	inhalation	LC50 Rat: 450 ppmV (4H)
Propan-2-ol	oral	LD50 Rabbit: 6410 mg/kg
	dermal	LD50 Rabbit: 12,800 mg/kg
	inhalation	LD50 Rabbit: 72.6 mg/L (4 H)
Dimethyl siloxane	oral	LD50 Rat: > 17,000 mg/kg
	dermal	LD50 Rabbit: > 2000 mg/kg
	inhalation	LC50 Rat: > 978,000 mg/m ³ (7.5 hours)

Skin corrosion/irritation

Assessment:

Causes skin irritation.

Product data:

No data available.

Substance data:

Name	Result
2-Butoxyethanol	Causes skin irritation
Functional-siloxanes, terminated	Causes severe skin burns.

Serious eye damage/irritation

Assessment:

Causes serious eye irritation.

Product data:

No data available.

Substance data:

Name	Result
2-Butoxyethanol	Causes serious eye irritation
Surfactant blend	Causes serious eye damage.
Propan-2-ol	Causes serious eye irritation.
Functional-siloxanes, terminated	Causes serious eye damage.

Respiratory or skin sensitization

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

International Agency for Research on Cancer (IARC):

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.20.2020

Page 9 of 13

Sunset Glow

Name	Classification
Water	Not Applicable
2-Butoxyethanol	Group 3
Surfactant blend	Not Applicable
Propan-2-ol	Group 3
Dimethyl siloxane	Not Applicable

National Toxicology Program (NTP):

Name	Classification
Water	Not Applicable
2-Butoxyethanol	Not Applicable
Surfactant blend	Not Applicable
Propan-2-ol	Not Applicable
Dimethyl siloxane	Not Applicable

OSHA Carcinogens: Not applicable

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Propan-2-ol	May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.20.2020

Page 10 of 13

Sunset Glow

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
2-Butoxyethanol	EC50 Daphnia magna (Water flea): 1,550 mg/L (48 h)

Chronic (long-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
2-Butoxyethanol	NOEC Brachydanio rerio: 100 mg/L (21 Days)

Persistence and degradability

Product data: No data available.

Substance data:

Name	Result
2-Butoxyethanol	Readily biodegradable.
Propan-2-ol	Readily biodegradable in water.

Bioaccumulative potential

Product data: No data available.

Substance data:

Name	Result
2-Butoxyethanol	Not expected to bioaccumulate (log Kow = 0.83).
Propan-2-ol	Not expected to bioaccumulate (log Kow: 0.05).

Mobility in soil

Product data: No data available.

Substance data: No data available.

Results of PBT and vPvB assessment

Product data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

Substance data:

PBT assessment:

2-Butoxyethanol	This substance is not PBT.
Propan-2-ol	This substance is not PBT.

vPvB assessment:

2-Butoxyethanol	This substance is not vPvB.
Propan-2-ol	This substance is not vPvB.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.20.2020

Page 11 of 13

Sunset Glow

Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

Contaminated packages:

Not determined or not applicable.

SECTION 14: Transport information

United States Transportation of dangerous goods (49 CFR DOT)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Maritime Dangerous Goods (IMDG)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

SECTION 15: Regulatory information

United States regulations

Inventory listing (TSCA): All ingredients are listed or exempt.

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export notification under TSCA Section 12(b): None of the ingredients are listed.

SARA Section 302 extremely hazardous substances: None of the ingredients are listed.

SARA Section 313 toxic chemicals:

7732-18-5	Water	Not Listed
111-76-2	2-Butoxyethanol	Not Listed

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.20.2020

Page 12 of 13

Sunset Glow

Proprietary	Surfactant blend	Not Listed
67-63-0	Propan-2-ol	Listed
63148-62-9	Dimethyl siloxane	Not Listed

CERCLA: None of the ingredients are listed.

RCRA: None of the ingredients are listed.

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know:

7732-18-5	Water	Not Listed
111-76-2	2-Butoxyethanol	Listed
Proprietary	Surfactant blend	Not Listed
67-63-0	Propan-2-ol	Listed
63148-62-9	Dimethyl siloxane	Not Listed

New Jersey Right to Know:

7732-18-5	Water	Not Listed
111-76-2	2-Butoxyethanol	Listed
Proprietary	Surfactant blend	Not Listed
67-63-0	Propan-2-ol	Listed
63148-62-9	Dimethyl siloxane	Not Listed

New York Right to Know:

7732-18-5	Water	Not Listed
111-76-2	2-Butoxyethanol	Listed
Proprietary	Surfactant blend	Not Listed
67-63-0	Propan-2-ol	Listed
63148-62-9	Dimethyl siloxane	Not Listed

Pennsylvania Right to Know:

7732-18-5	Water	Not Listed
111-76-2	2-Butoxyethanol	Listed
Proprietary	Surfactant blend	Not Listed
67-63-0	Propan-2-ol	Listed
63148-62-9	Dimethyl siloxane	Not Listed

California Proposition 65: None of the ingredients are listed.

SECTION 16: Other information

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.20.2020

Page 13 of 13

Sunset Glow

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 0-0-0

HMIS: 1-0-0-B

Initial preparation date: 07.20.2020

End of Safety Data Sheet